


# 15" Capacitive IP65 HB Touch Monitor

FT15TMCAPHBOB



- Anti-glare surface treatment (chemical etching)
- 10-Finger-Multi Touch Capacitive Touch Panel
- 1.1mm cover glass with 7H surface hardness
- Optically bonded Touch Panel to LCD Panel
- Comprehensive IP65 protection, including water- and dustproof
- 1000+ cd/m<sup>2</sup> brightness for increased visibility
- Extended voltage input 8~36V
- Integrated audio speakers (2x2w)
- All-in-One cable (2m length, attached to monitor)
- VESA 100 mounting
- 2 years guarantee (24/7 usage)



faytech's Capacitive IP65 High Brightness Touch Monitors have a modern sleek look with its flat edge to edge front glass and complete IP65 proof aluminum case. This device has capacitive 10-finger multitouch, glass front reaching MosH 7 and VESA 100 screw patterns on the back, ensuring a solid fixation in any environment. It is the perfect solution for industrial, rough and outdoor environments.

### Advantages of these devices:





- Increased brightness (1000+ cd/m<sup>2</sup>)
- Complete IP65 protection (dust- and waterproof)
- All-in-One cable - HDMI, USB-Touch and 8-36V DC-In

These devices are the perfect choice for a wide variety of applications, such as control panels in industrial fields, POS systems, digital signage and many more!

On top of that, there is a wide array of customizations options available, such as connectors, casing or added peripherals.



Legend / Notes	
Applicable to version 1	(v1)
Applicable to version 2	(v2)
Applicable to all Versions	None



<b>Product name</b>				<b>15" Capacitive IP65 HB Touch Monitor</b>			
<b>Article code / EAN number</b>				<b>FT15TMCAPHBOB / 6920734015207</b>			
Global Article Code	European Article Code	Release date (D/M/Y)	Version*	Global Article Code	European Article Code	Release date (D/M/Y)	Version*
210205005939	1010501158	20/03/2021	v1				
3030511147	1010502597	25/04/2022	v2				

<b>IP rating</b>	
IP65	

<b>LCD Panel</b>	
Screen diagonal (Inch/cm)	15/38.10
Display active screen size (cm)	30.40×22.80
Aspect ratio	4:3
Physical resolution	1024×768
Maximum showable resolution	1920×1080
Colours displayed	16.7M
Brightness (cd/m²)	1000+
Contrast	700:1
Typical reaction time Tr/ Tf (ms)	8/12
Visual Angle horizontal/vertical (°)	160/160
Backlight / Backlight Lifetime (hours)	LED / 30,000



<b>External Connectors</b>	
All-In-One cable HDMI version	1x HDMI
	1x USB-Touch
	1x 8-36V DC-IN

<b>Touch Panel</b>	
Touch Technology	Projected Capacitive 10-Point Multitouch
Touch Panel Drivers	Windows; Linux; Mac; Android
Touch Life (Contacts)	Unlimited
Surface Hardness	7H
Surface Treatment	Anti-glare (chemically etched)
Glass Strengthening	Chemically Strengthened

<b>Operation / Mechanical</b>	
Operating Temperature (°C)	-20 ~ +75
Humidity Range (RH)	10% - 90%
Net weight (kg)	3.00
Gross weight (kg)	4.50 (incl. cartonnage)
Housing material	Rubber frame, Aluminum back case
Housing (mm) L × W × H	359.0 × 291.0 × 55.5
Cut-out for clamp supports (mm) L × H	335.0 × 274.0
Max. wall thickness for clamp supports (mm)	5.0
Amount of clamps required	6
Mounting	VESA 100

<b>Power</b>	
Power Indicator	Green LED
Power Supply	100-240V ACDC active switching; 12V DC-Out
Working Power (V)	9~36
Power Consumption (W)	20
Stand-By Consumption (W)	<1

<b>Included in the Delivery</b>	
Power Supply (see Power section)	
Short Installation Manual	
All-In-One cable - 2m length, attached to monitor (length can be customized upon request)	



Tolerance: ± 1mm

## Update Notes:

\* Only the latest version can be ordered, previous versions are only for historic reference.

### Version:

### Changes:

- |           |   |  |
|-----------|---|--|
| <b>v2</b> | - | Update of internal wiring and components                         |
| <b>v1</b> | - | First version<br>( <i>v1 &amp; v2 drawing on previous page</i> ) |

## Corporate Headquarters

### faytech AG

Bischhäuser Aue 10  
37213 Witzenhausen  
Germany

[support@faytech.com](mailto:support@faytech.com)  
[contact@faytech.com](mailto:contact@faytech.com)  
[www.faytech.com](http://www.faytech.com)

China: +86 755 8958 0612  
Germany: +49 5542 30374 10  
USA: +1 646 843 0877  
India: +91 11 49707436  
Japan: +070 4127 5167